

THE INDUSTRY STANDARD

For over 30 years, Jandy valves have been the undisputed leader in the pool and spa industry. Our commitment to quality makes for easier, problem-free installations. Jandy valves share one thing in common – dependability. Dependability begins with top-of-the-line materials and rigorous quality control standards. Superior quality and plumbing versatility make Jandy valves the number one choice of pool and spa professionals everywhere.



INDEX TAB*



PLACARD*

*On 2 1/2" x 3" valve only



Jandy Valves with Never Lube® Technology

The Never Lube Valve is completely maintenance-free and built from the toughest CPVC material. It can withstand extreme chemical and temperature fluctuations without ever leaking, cracking or breaking.

- Available in 1 1/2" x 2", 2" x 2 1/2", and 2 1/2" x 3" sizes for easy use in conjunction with the Jandy Valve® Actuator for automatic operation
- The large 2-port and 3-port diverter valves are both 2 1/2" x 3", making them the largest valves on the market
- Included placards* label the valve position
- Never requires lubrication
- Adjustable-stop feature allows for custom and worry-free flow adjustment
- Never Lube Diverter Valves can handle flow rates up to 170 GPM with minimal head loss, making them great for spas and water features that require high flow rates
- All Never Lube Diverter Valves are lifetime guaranteed



Gray Valve

This tough and economical workhorse diverter valve is the standard-bearer valve of Jandy.

- Can be lubricated without disassembly
- Made of super-durable CPVC
- Comes with a 20-year track record of proven reliability
- Available in 1 1/2" x 2" and 2" x 2 1/2" sizes



Jandy Valve Actuator (JVA)

- Fully adjustable actuator
- Fits all Jandy Never Lube and Gray 2- and 3-port diverter valves in 1 1/2" x 2", 2" x 2 1/2" and 2 1/2" x 3" sizes
- Works with AquaLink® control systems
- Available in 24V model



Check Valve

All Jandy Check Valves are designed with a clear lid and a red seal plate for easy inspection and have a unique swing/spring design.

- Made of the toughest CPVC material
- Easily disassemble for clearing debris
- Large 2 1/2" x 3" dimension is designed for high flow rates
- 2 1/2" dimension allows for easy plumbing at the equipment pad to other Jandy universal union connections
- Large Jandy Check Valve can handle flow rates up to 170 gallons per minute with minimal head loss, making it great for spas and water features that require high flow rates
- Check Valves are available in straight-through or 90° models and 1 1/2" x 2" or 2" x 2 1/2" sizes



Heavy Duty Ball Valves

- Available in single-union and double-union designs
- Durable gray PVC body construction
- "Antiblock" system that avoids ball blockage
- Available in size range from 1/2" up to 4"